



# TITLE OF THE INVENTION

DRIVING METHOD FOR FLAT-PANEL DISPLAY DEVICE

## CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application is based upon and claims the benefit of priority from the prior Japanese Patent Application No. 2001-030612, filed February 7, 2001, the entire contents of which are incorporated herein by reference.

## BACKGROUND OF THE INVENTION

### 10 1. Field of the Invention

The present invention relates to a method for driving a flat-panel display device with the potential of a counter electrode to be inverted with respect to a reference potential.

### 15 2. Description of the Related Art

In general, in a liquid crystal display device, to prevent degradation of the characteristics of its liquid crystal layer, the polarity of a voltage applied across the liquid crystal layer is inverted periodically. The method of inverting the polarity of the liquid crystal application voltage for every predetermined number of frames is called "frame inversion driving". Actually, however, flicker is caused due to asymmetry of the voltage between the positive and negative polarities. As a driving method capable of reducing the flicker, "H-line inversion driving" and "HV inversion driving" are known. In the

20

25

10065565.052802

H-line inversion driving method, the polarity of the liquid crystal application voltage is inverted for every one or more predetermined gate lines (rows).

In the HV inversion driving method, the polarity of

5 the liquid crystal application voltage is inverted for every pixel. During the H-line inversion driving or HV inversion driving method, the potential of each signal line is switched for every predetermined number of

10 horizontal lines to a polarity positive or negative to the potential of the counter electrode, so as to invert the polarity of the liquid crystal application voltage.

Assume that switching is performed for each horizontal line, for example. During one frame, signals of a polarity positive to the potential of the counter

15 electrode are written into pixel electrodes assigned to the odd-numbered gate lines, and signals of a polarity negative to the potential of the counter electrode are written into pixel electrodes assigned to the even-

20 numbered gate lines. During the next frame, signals of a polarity negative to the potential of the counter electrode are written into the pixel electrodes

assigned to the odd-numbered gate lines, and signals of a polarity positive to the potential of the counter electrode are written into the pixel electrodes

25 assigned to the even-numbered gate lines.

With above-mentioned methods, the polarity of the liquid crystal application voltage is inverted,

1006655-052802

and this enables reduction of flicker to be observed on the screen due to the characteristics or imperfections of pixels.

In general, a voltage of about 4V is required for driving a liquid crystal. Therefore, when the potential of the counter electrode is fixed to perform the above-mentioned polarity inversion driving method, a dynamic range of 8V and accuracy in the voltage of each polarity are required for the output of the driving circuit. This causes a problem such as an increase in the consumption of power.

In contrast, if the polarity of the counter electrode potential is simultaneously inverted to decrease the output range of the driving circuit, the power consumption can be reduced accordingly and the voltage amplitude on the video bus can also be reduced.

FIG. 11 is a timing chart for operation timings of various components obtained in a (1H/common inversion driving) case where the counter electrode potential is inverted for every horizontal line while the H-line inversion driving method is performed using one-point-at-a-time scanning. In FIG. 11, a display signal voltage on a display signal bus, a control signal (shift pulse) SPj input to a j-th analog switch ASWj, a j-th signal line potential VSj, and the counter electrode potential Vcom are arranged from top down. As shown in FIG. 11, the counter electrode potential

Vcom is inverted with respect to the half value of the maximum amplitude of the signal line potential to have the maximum and minimum levels of 5V and 0V. Assume here that the liquid crystal application voltage is regarded as being of a positive polarity when the counter electrode potential Vcom is set at the minimum level, and of a negative polarity when the counter electrode potential Vcom is set at the maximum level. When the normally white display mode is used, the signal line potential of the positive polarity is set at 0.5V for providing a display state of white and at 4V for providing a display state of black, whereas the signal line potential of the negative polarity is set at 4.5V for providing a display state of white and at 1V for providing a display state of black. In this display device, transition of each signal line potential becomes to the maximum, for example when both of two adjacent horizontal lines are set into the display state of black. In this case, it is expected that the signal line potential varies from 4V to 1V, and the maximum transition becomes to 3V.

Actually, however, the counter electrode potential is inverted while the signal lines are in a floating state. Therefore, the potential of each signal line varies with the potential of the counter electrode due to coupling between the counter electrode and the signal line. As a result, the signal line potential

10065565.052802

is shifted by + 5V in accordance with the counter electrode potential, and reaches 9V. The signal line holds 9V until the next display signal is written thereto. In this state, if a signal line potential of 1V is written to set two adjacent horizontal lines at the black level, the signal line potential shifts at a variation range of 8V due to the inversion of the counter electrode potential.

As described above, in the case where H/common inversion driving is performed in the conventional liquid crystal display device, a variation in potential occurs in each signal line when the counter electrode potential is inverted for each predetermined horizontal line and frame, which increases the variation range of the signal line potential for the next writing operation. For example, the closer to black the display color of display pixels adjacent in a row direction, the greater the variation of the signal line potential and hence the higher the possibility of a defective display by the influence of the potential variation in each signal line.

#### BRIEF SUMMARY OF THE INVENTION

The present invention has been developed in light of the above problem, and aims to provide a driving method for a flat-panel display device, which can suppress variation in the potential of each signal line.

The present invention provides a driving method for a flat-panel display device which includes a plurality of signal lines, a plurality of gate lines substantially perpendicular to the signal lines, a plurality of switching elements provided near intersections of the signal lines and the gate lines, a plurality of pixel electrodes connected via the switching elements, and a counter electrode opposed to the pixel electrodes, and in which a display signal is sequentially supplied to the signal lines and a potential of the counter electrode is inverted with respect to a reference potential for every predetermined number of horizontal and vertical scanning periods or for every predetermined number of vertical scanning periods so as to perform a display operation, the driving method being characterized by comprising fixing all the signal lines to a predetermined potential and inverting the potential of the counter electrode during a horizontal or vertical blanking period subsequent to a horizontal or vertical display period.

According to the present invention, the potential of each signal line can be suppressed from varying upon inversion of the counter electrode potential. Further, the consumption of power can be reduced. In addition, the variation range in the potential of each signal line can be reduced, and hence suppress the occurrence

of a defective display due to the potential variations of the signal lines.

Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out hereinafter.

10 BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate presently preferred embodiments of the invention, and together with the general description given above and the detailed description of the preferred embodiments given below, serve to explain the principles of the invention.

FIG. 1 is a plan view schematically illustrating the configuration of a liquid crystal display device according to an embodiment of the invention;

FIG. 2 is a timing chart illustrating the operation of the liquid crystal display device shown in FIG. 1;

FIG. 3 is a schematic plan view illustrating the configuration of a liquid crystal display device according to another embodiment of the invention;

FIG. 4 is a timing chart for components of

10066565.052802

the liquid crystal display device shown in FIG. 3;

FIG. 5 is a view illustrating a first modification of a part incorporated in the liquid crystal display devices shown in FIGS. 1 and 3;

5        FIG. 6 is a view illustrating a second modification of the part incorporated in the liquid crystal display device shown in FIGS. 1 and 3;

10        FIG. 7 is a view illustrating a third modification of the part incorporated in the liquid crystal display devices shown in FIGS. 1 and 3;

FIG. 8 is a timing chart illustrating the operation of the modification shown in FIG. 7;

15        FIG. 9 is a view illustrating the polarity of each liquid crystal application voltage of the liquid crystal display device shown in FIGS. 1 and 3;

FIG. 10 is a view illustrating a modification concerning the polarity of each liquid crystal application voltage shown in FIG. 9; and

20        FIG. 11 is a timing chart for components of a conventional liquid crystal display device.

#### DETAILED DESCRIPTION OF THE INVENTION

A liquid crystal display device according to an embodiment of the present invention will be described with reference to the accompanying drawings.

25        The liquid crystal display device 1 comprises a liquid crystal panel LCP having a structure in which a liquid crystal layer is held and sealed between

1006655-052302



an array substrate and a counter substrate opposed thereto, and a display circuit for driving the liquid crystal panel LCP.

The array substrate comprises a pixel array section which includes signal lines  $S_j$  and gate lines  $G_i$  arranged on a transparent insulation plate made of, for example, glass and serves as a display area; a signal line driving circuit 20 for driving each signal line  $S_j$ ; and a gate line driving circuit 10 for driving each gate line  $G_i$ . These components are integrally formed with the transparent insulation plate. Further, in the counter substrate, a light-shielding layer, a color filter layer and a counter electrode are provided on a transparent insulation plate. The liquid crystal panel is constructed such that the pixel array section and counter electrode face each other, and the liquid crystal layer is held between the substrates.

The display circuit includes a controller section CTL which receives a digital display signal DATA, a clock CLK, a synchronization signal ENAB or the like supplied from an external signal source S such as a personal computer, and performs a digital processing of generating control signals (such as a reset signal) for driving the liquid crystal display panel LCP, rearrangement of the digital display signal DATA, or the like. The display circuit also includes a D/A converter DAC for converting the digital display signal

10066565.052802

DATA into an analog form; a common circuit for  
outputting a counter electrode potential; and a DC/DC  
converter DC/DC for generating, from a power source  
potential VDD from the signal source S, various power  
5 source potentials required for driving the liquid  
crystal panel LCP. The controller section CTL, common  
circuit and DC/DC converter DC/DC are provided on  
a printed circuit board PCB, while the D/A converter  
DAC is provided as an IC mounted on a flexible printed  
10 circuit FPC. The display circuit and liquid crystal  
display panel LCP are electrically connected via the  
flexible printed circuit FPC.

FIG. 1 is a view schematically showing the  
configuration of the liquid crystal display device 1.  
15 As shown in FIG. 1, a plurality of liquid crystal  
display pixels  $P_{ij}$  ( $i = 1, 2, \dots, m$ ;  $j = 1, 2, \dots, n$ )  
are arranged in a matrix on the liquid crystal display  
panel, each liquid crystal display pixel  $P_{ij}$  being  
connected to a pixel TFT (Thin Film Transistor)  $T_{ij}$ .  
20 The gates of pixel TFTs arranged in each row are  
commonly connected to a corresponding gate line  $G_i$ ,  
while the drains of pixel TFTs arranged in each column  
are commonly connected to a corresponding signal line  
 $S_j$ . Further, each liquid crystal display pixel  $P_{ij}$  is  
25 formed of a pixel electrode connected to a correspond-  
ing pixel TFT  $T_{ij}$ , the counter electrode opposed to  
the pixel electrode and connected to the common circuit

commonly provided for all the liquid crystal display pixels  $P_{ij}$ ; and the liquid crystal layer held between the pixel electrode and counter electrode. Storage capacitances  $CS_{ij}$  parallel to the liquid crystal display pixels  $P_{ij}$  are connected to the pixel TFTs  $T_{ij}$ . The storage capacitances  $CS_{ij}$  arranged in each row are commonly connected to a corresponding storage capacitance line  $CL_i$ .

The gate line driving circuit 10 includes a shift register, and is arranged to sequentially output a row-scanning signal to the gate lines  $G_i$  on the basis of a vertical synchronization signal and vertical clock signal.

The signal line driving circuit 20 includes a shift register and analog switches  $ASW_j$ , and is arranged to perform serial-parallel conversion of an analog display signal input from the display circuit on the external substrate, thereby outputting data on a display signal bus  $VL$  to a corresponding signal line.

Each signal line  $S_j$  has a switching element  $SW_j$  at its end, the switching element having its drain commonly connected to a signal line voltage regulating power source and its gate connected to a reset terminal.

A description will now be given of a method for driving the liquid crystal display panel of the aforementioned circuit structure with a use of

10065555.052802

one-point-at-a-time scanning. The H/common inversion driving method is employed in this embodiment, thus the potential of the counter electrode is inverted for every predetermined number of horizontal periods.

5 Specifically, the liquid crystal application voltage is inverted for every predetermined horizontal line and for every frame period. In addition, the polarity of the counter electrode potential is concurrently inverted for every horizontal line.

10 Assume that one horizontal display period is the period from the start of writing to an initially selected signal line, to the end of writing to a lastly selected signal line. More specifically, assume here that the one horizontal display period is the period  
15 from a time that a shift pulse SP1 for turning on the first-column analog switch ASW1 of each horizontal line has been supplied, to the time that a shift pulse SPn for turning off the last-column analog switch ASWn of each horizontal line has been supplied, and that a  
20 horizontal blanking period is the period from the end of one horizontal display period to the start of the next one horizontal display period. In other words, one horizontal scanning period is formed of the  
25 horizontal display period and horizontal blanking period.

Accordingly, the polarity of the signal line potential is inverted along with that of the counter

1006555.052302

electrode potential during the horizontal blanking period. This will be described in detail.

FIG. 2 is a timing chart illustrating the operation of the liquid crystal display device.

5 In FIG. 2, a scanning signal for the  $i$ -th row, a scanning signal for the  $(i+1)$ -th row, an analog display signal, a shift pulse  $SP_j$  input to an analog switch  $ASW_j$  of the  $j$ -th stage, a reset signal input to the gate of a switching element, a signal line potential for the  $j$ -th column, and the counter electrode potential  $V_{com}$  are arranged from top down.

10 When a start pulse has been input at a certain timing, a necessary number of registers assigned to the signal lines sequentially output a shift pulse  $SP_j$  obtained by shifting the start pulse in synchronism with a shift clock. The shift pulse  $SP_j$  output from each register is input to the control terminal of a corresponding analog switch  $ASW_j$ . When the shift pulse  $SP_j$  has been input to the control terminal, the analog switch  $ASW_j$  is turned on (closed), thereby supplying an analog display signal on the display signal bus VL to a corresponding signal line  $S_j$ .

15 As the above operation is repeated, each analog switch  $ASW_j$  is turned on substantially at the same time that the shift pulse  $SP_j$  is output from a corresponding register, thereby supplying a corresponding analog signal on the display signal bus VL to a signal line  $S_j$

10066565 " 052802

connected to the analog switch ASWj.

As shown in FIG. 2, each signal line Sj holds a potential written immediately before the turn-off of a corresponding analog switch ASWj.

5           When a shift pulse SPn has been output from the last-stage register, a reset signal is supplied to the reset terminals of the switching elements SWj for fixing the signal line potential. As a result, the switching elements SWj are turned ON while all the analog switches ASWj are in the OFF state, whereby the potential of each signal line is fixed to a desired potential output from the signal line voltage regulating power source during each horizontal blanking period. Further, in synchronism with this timing, 10 the counter electrode potential Vcom is inverted with respect to that in the preceding horizontal display period. 15

Since the pixel TFTs of a corresponding row are turned off by means of a scanning signal before the reset signal is input, the liquid crystal application voltage is maintained at a desired value based on a display signal. 20

After the horizontal blanking period finishes, a start pulse is input again and the registers of the shift register resume their shifting operations for the start pulse. 25

As described above, since all the signal lines

10066565-052802

are fixed to a desired potential, e.g. an intermediate potential in this embodiment, during the horizontal blanking period, variation in the potential of each signal line, due to the coupling of the counter electrode and the signal line, can be suppressed when the counter electrode potential is inverted, thereby reducing the consumption of power. Further, since the variation range of each signal line potential after the blanking period is small, the signal line can be promptly set at a desired potential.

For example, if the voltage of a display signal on a display signal bus varies within the amplitude of 1 to 4V as in the conventional case, all the potentials of the signal lines are fixed to the intermediate potential of the display signal during the horizontal blanking period in the embodiment. The intermediate potential means here a potential near the intermediate level of the maximum and minimum levels of the display signal, and is set at, for example, 2.5V in the above amplitude.

Since the signal line is thus fixed to the intermediate potential of 2.5V when the counter electrode potential  $V_{com}$  is inverted, the variations in the potential of each signal line due to the coupling of the counter electrode and the signal line can be suppressed.

If black is displayed after fixing to the

100665565 . 052802

intermediate potential of 2.5V, the variation range of the signal line potential can be reduced to 1.5V, which is the difference between the intermediate potential of 2.5V and the potential used for displaying black in the negative polarity driving state, 1V. Thus, the signal line potential is prevented from being driven out of time, thereby suppressing variations in contrast and hence enhancing the quality of display.

A liquid crystal display device according to another embodiment of the invention will be described. In this liquid crystal display device, a desired potential is written during the horizontal blanking period via each analog switch ASWj of a signal line driving circuit to thereby fix a corresponding signal line potential.

FIG. 3 is a schematic view illustrating the structure of the liquid crystal display device 1, and FIG. 4 is a timing chart illustrating the operation of the liquid crystal display device 1. In FIG. 4, an analog display signal, a shift pulse SPj input to each analog switch ASWj, a signal line potential for the j-th column, and the counter electrode potential Vcom are arranged from top down in a case where the H/common inversion driving method is performed with a use of one-point-at-a-time scanning.

As in the first embodiment, when a start pulse has been input at a certain timing, a necessary number of

10065565.052802



registers assigned to the signal lines sequentially  
output a shift pulse SPj obtained by shifting the start  
pulse in synchronism with a shift clock. The shift  
pulse SPj output from each register is input to the  
5 control terminal of a corresponding analog switch ASWj.  
When the shift pulse SPj has been input to the control  
terminal, the analog switch ASWj is turned on (closed),  
thereby supplying an analog display signal on the  
display signal bus VL to a corresponding signal line  
10 Sj. As the above operation is repeated, each analog  
switch ASWj is turned on substantially at the same time  
that the shift pulse SPj is output from a corresponding  
register, thereby supplying a corresponding analog  
signal on the display signal bus VL to a signal line  
15 Sj connected to the analog switch ASWj. As shown in  
FIG. 4, each signal line Sj holds a potential written  
immediately before the turn-off of a corresponding  
analog switch ASWj.

When one horizontal display period has finished  
20 and a horizontal blanking period has started, a shift  
pulse SPj for turning one each analog switch ASWj is  
input to all the analog switches, thereby writing the  
same signal to all the signal lines. While all the  
analog switches ASWj are in the ON state, each signal  
25 line potential is fixed to a desired potential, e.g.  
an intermediate potential. Further, in synchronism  
with this timing, the counter electrode potential Vcom

10065565-052802

is inverted with respect to that in the preceding horizontal display period.

After the horizontal blanking period finishes, a start pulse is input again and the registers of the shift register resume their shifting operations for the start pulse.

As described above, since all the signal lines are fixed to a desired potential, e.g. an intermediate potential in this embodiment, during the horizontal blanking period, variations in the potential of each signal line due to the coupling of the counter electrode and the signal line can be suppressed when the counter electrode potential is inverted, thereby reducing the consumption of power. Further, since the variation range of each signal line potential after the blanking period is small, the signal lines can be promptly set at a desired potential.

Although in the above embodiment, a description has been given of using a display signal of an analog form input to the array substrate, a digital signal input from the outside may be converted into an analog signal by the D/A converter provided on the array substrate, as shown in FIG. 5. The D/A converter DAC may be formed integral with the glass plate in the same process as the pixel TFTs of the display area or the driving circuit formed on the array substrate. Alternatively, the converter may be an IC chip, which

10065555-052802

is formed independently of the glass plate and provided thereon.

Also, as shown in FIG. 6, the structure may be modified such that a digital display signal from the outside is subjected to serial-parallel conversion and then converted into an analog form by D/A converters DAC each of which is provided for a predetermined number of signal lines and distributes a result of conversion to the respective signal lines. Each D/A converter DAC is composed of polysilicon TFTs formed integral with the glass plate in the same process as the pixel TFTs of the display area.

In this case, each D/A converters DAC is connected to three signal lines forming a group for simultaneous selection and sequentially selects the three signal lines by time-division. In other words, the signal lines other than a selected one of the grouped signal lines are all in the floating state.

Thus, in the case where the D/A converter DAC is provided along with the signal lines on the same substrate, a display signal of a digital form can be supplied to the array substrate, and display of influence due to noise can be suppressed.

Furthermore, as shown in FIG. 7, the signal lines may be divided into groups each including a predetermined number of signal lines, and be driven in units of groups. In other words, the analog switches

10065555.052802

corresponding to the signal lines of a selected group are simultaneously turned on, while the signal lines of the other groups not selected are all in the floating state.

5           Thus, the one-point-at-a-time scanning does not always mean a system in which pixels are sequentially selected one by one at every horizontal line, but can include a time-divisional driving system in which a plurality of pixels simultaneously selected for one  
10           line are selectively driven during one horizontal scanning period. This time-divisional driving system may include a system in which signal line selection is executed in units of signal line groups, or a system in which all signal line groups are simultaneously  
15           selected, and the signal lines of each group are sequentially selected by time-division, as is described above.

          Furthermore, as shown in FIG. 7, the analog switches ASWj, incorporated in the signal-line-driving  
20           circuit, may be formed on the glass plate alone, and other circuit elements, including the D/A converter, may be arranged externally. The number of outputs of the D/A converter DAC is identical to that of the signal lines belonging to all the signal line groups.

25           FIG. 8 is a timing chart illustrating the operation of the liquid crystal display device of the structure shown in FIG. 7. In FIG. 8, a scanning

1006565.052302

signal for the  $i$ -th row, a scanning signal for the  
( $i+1$ )-th row, an analog display signal on a display  
signal bus connected to an  $S$ -th column ( $S = 2, 26, 50,$   
...,  $n-22$ ) signal line, a shift pulse  $SP_j$  input to  
5 an analog switch  $ASW_j$  of the  $j$ -th stage, the counter  
electrode potential  $V_{com}$ , a potential  $VS_2$  applied to  
the 2nd signal line, and a potential  $VS_{26}$  applied  
to the 26-th signal line are arranged from top down.  
Thus, the writing order of a display signal in the  
10 signal lines may be reversed at every horizontal line.  
Although FIG. 8 shows that the writing order is  
reversed for every horizontal line, it may be reversed  
for every predetermined number of horizontal lines.  
Yet further, the writing order can be reversed in units  
15 of frames, in addition to the reverse in units of  
horizontal lines. This method of scanning enables  
variations in the potential of each storage capacitance  
line, if they occur, to be offset using the entire  
display screen, thereby realizing satisfactory image  
20 display.

Moreover, the above-described embodiments explain  
that the counter electrode potential is inverted for  
every horizontal scanning period, as shown in FIG. 9,  
but the invention is not limited to this, and is also  
25 applicable to the H/common inversion driving method in  
which the counter electrode potential is switched for  
every predetermined number of horizontal scanning

1006655.052802

periods. For example, as shown in FIG. 10, in a frame inversion driving method, the counter electrode potential may be switched in units of frames. In this case, the period for wiring a display signal corresponding to one frame is set as a vertical display period, and the counter electrode potential is inverted during the vertical blanking period subsequent to the vertical display period. Thus, the present invention can be applied to various types of common inversion driving. This means that it is important to fix the signal line potential to a predetermined value when the counter electrode potential is inverted.

Furthermore, although each of the above embodiments uses a liquid crystal display device as an example, the invention is not limited to this, but is also applicable to various types of flat-panel display devices in which the common inversion driving is performed with a use of the one-point-at-a-time scanning.

In addition, in each of the above embodiments, a description has been given of a flat-panel display device in which a counter electrode is formed on one of two transparent insulation substrates, and pixel electrodes are formed on the other transparent insulation substrate. However, the invention is also applicable to an IPS (In Plane Switching) flat-panel display device, in which both the counter electrode and

10066565-052302

pixel electrodes are provided on the one substrate.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to  
5 the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

10065565 . 052802